



## GP-FLL Product Specification

<b>LED Power:</b>	<b>40 W - 50 W</b>
<b>Operating Voltage:</b>	110 - 277 VAC 50 Hz/60 Hz 12 - 24 VDC
<b>Power Efficiency:</b>	>0.9
<b>Power Factor:</b>	>0.98
<b>Luminous Efficiency:</b>	100 lm/w
<b>Light Efficiency:</b>	>90%
<b>Color Rendering Index:</b>	Ra>80
<b>Color Temperature:</b>	2700K - 7000K
<b>Working Environment:</b>	-40 F to 131 F
<b>Protection Grade:</b>	IP65
<b>Life Span:</b>	>50,000 hours
<b>Weight:</b>	7.26 lbs
<b>Dimensions:</b>	11.42" x 9.29" x 8.11"
<b>Driver UL Number:</b>	UL8750 / UL60950-1

Green Power USA  
A GP-DENLED COMPANY  
1799 Kiowa Blvd. Suite 110  
Lake Havasu City, AZ 86403  
928.680.1699

Information:  
info@gp-denled.com

Website:  
greenpowerrusa.us

Made in the USA

Assembly Center:  
Newport Business Park  
3176 Pullman St. Suite 112  
Costa Mesa, CA 92626  
714.557.9100



**GREEN POWER USA**