



## GP-T8 Product Specification

<b>Wattage:</b>	<b>22W Constant Current</b>
<b>AC Input Voltage/Frequency:</b>	110 - 277 VAC (60 Hz)
<b>DC Output Voltage:</b>	36 VDC/700 mA, Constant Current
<b>Dimensions:</b>	1 Inch Diameter
<b>Base Length:</b>	47.75 Inches
<b>Working Temperature:</b>	-30 ~ +50 Degrees C
<b>LED:</b>	Nichia
<b>Color Temperature:</b>	3500 - 5000 Kelvin (other CCT available on special order)
<b>CRI:</b>	84 - 86
<b>Life Span:</b>	50,000 - 100,000 hours
<b>Warranty:</b>	Standard 5 Year Warranty
<b>Body:</b>	Bottom half used as heat sink is made of aluminum; Top half used as lens is transparent plastic, CAN09-052375.001 grains
<b>Bi-Pin Base:</b>	Standard
<b>LED Angle:</b>	120 degrees
<b>LED Count:</b>	20 x 1 watts
<b>Lens Colors (suffix):</b>	Clear -C Soft White -SW Frosted White -FW
<b>Dimmable:</b>	Yes
<b>Net Weight:</b>	0.65 lbs
<b>Individual Shipping Carton:</b>	49" long x 1.5" square
<b>Product Category:</b>	OOLV3 - Lamps, Self Ballasted, Light-Emitting Diode Type - Unlisted Component
<b>RoHS Compliant:</b>	Yes
<b>Driver UL Number:</b>	UL1993 / UL8750 / ULE342708

Green Power USA  
 A GP-DENLED COMPANY  
 1799 Kiowa Blvd, Suite 110  
 Lake Havasu City, AZ 86403  
 928.680.1699

Assembly Center:  
 Newport Business Park  
 3176 Pullman St. Suite 112  
 Costa Mesa, CA 92626  
 714.557.9100

Information:  
[info@gp-denled.com](mailto:info@gp-denled.com)

Website:  
[greenpowewrusa.us](http://greenpowewrusa.us)

Made in the USA



**GREEN POWER USA**